



KEY FEATURES



10BB Half-cut Cell Technology

< ≤



Industry Leading High Yield



Excellent Anti-PID Performance



ELECTRICAL CHARACTERISTICS

| Testing Condition | STC | NMOT | STC | NMOT | STC | NMOT | STC | NMOT | STC | NMOT |
|-------------------------------|-----|------|-----|------|-----|------|-----|------|-----|------|
| Maximum Power (Pmax/W) | | | | | | | | | | |
| Operating Voltage (Vmpp/V) | | | | | | | | | | |
| Operating Current (Impp/A) | | | | | | | | | | |
| Open-Circuit Voltage (Voc/V) | | | | | | | | | | |
| Short-Circuit Current (Isc/A) | | | | | | | | | | |
| Module Efficiency (%) | | | | | | | | | | |

STC: Irradiance 1000W/m², Spectra at AM1.5, Module Temperature 25 °C. Power output tolerance: 0~+5W, Test uncertainty for Pmax: ±3%
 NMOT: Irradiance 800W/m², Spectra at AM1.5, Ambient Temperature 20 °C, Wind speed 1m/s

REAR SIDE POWER GAIN (REFER TO THE ELECTRICAL CHARACTERISTICS)

| Parameter | STC | NMOT | STC | NMOT | STC | NMOT | STC | NMOT |
|-----------|-----|------|-----|------|-----|------|-----|------|
| Pmax gain | | | | | | | | |
| Pmax/W | | | | | | | | |
| Vmpp/V | | | | | | | | |
| Impp/A | | | | | | | | |
| Voc/V | | | | | | | | |
| Isc/A | | | | | | | | |

Temperature Coefficient of Pmax: α_{Pmax} / °C
 Temperature Coefficient of Voc: α_{Voc} / °C

Output Cables
