

# BIPRO


132-cell



## 产品特性



0



15 20 30



### 18BB半片电池技术

LID/LeTID 1% 0.4%



### 行业领先的发电效率增益

TOPCon LCOE



### 抗PID和低辐照度性能优异

192 PID



### 更广泛的应用性

## 电性能参数

	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
(Pmax/W)	690	526	695	531	700	534	705	540	710	543
(Vmpp/V)	40.00	37.70	40.30	37.90	40.50	38.00	40.70	38.30	40.90	38.50
(Impp/A)	17.23	13.95	17.25	14.00	17.29	14.04	17.33	14.08	17.36	14.12
(Voc/V)	47.90	45.40	48.30	45.90	48.60	46.10	48.80	46.30	49.00	46.50
(Isc/A)	18.25	14.71	18.28	14.72	18.32	14.76	18.36	14.80	18.40	14.83
(%)	22.20		22.40		22.50		22.70		22.90	

STC : 1000W/m<sup>2</sup>, AM1.5, 25 °C, 0~+5W ± 3%  
 NMOT( ) : 800W/m<sup>2</sup>, AM1.5, 20 °C, 1m/s

## 背面功率增益(以700W为例)

	5%	10%	15%	20%	25%
(Pmax/W)	735	770	805	840	875
(Vmpp/V)	40.50	40.50	40.50	40.50	40.50
(Impp/A)	18.15	19.02	19.88	20.75	21.61
(Voc/V)	48.60	48.60	48.60	48.60	48.60
(Isc/A)	19.24	20.15	21.07	21.98	22.90

## 机械参数

	N	18BB
	132 (6*22)	
	2384*1303*33mm (93.86*51.30*1.30 )	
	38.5kg (84.88lbs.)	
	2.0mm	
	2.0mm	
	IP68, 3	
	4mm <sup>2</sup> (IEC), 1.2AWG (UL) 350mm(+), 280mm(-)	
	T01/LJQ-3-CSY/MC4/MC4-EVO2	

## 应用条件

	1500V/DC
	-40°C~+85°C
	35A
	Class
	5400Pa 2400Pa
	80%± 5%


## 温度系数

Pmax	-0.29%/°C
Voc	-0.24%/°C
Isc	+0.043%/°C
NMOT	43± 2°C

## 包装

	33	33(USA)
(40'HC)	594	495

## I-V曲线



## 技术图

